




CLIOW THE NUMBERED DRAWMES IN SHADING THE HEAD.
CCUT OUT THE SHADED PART
OF THE NECK. TAKE OUT ENOUGH
WOOD ON EITHER SIDE OF THE
MECK SO THAT IT WILL BEPRACTICALLY SQUARE-.
CCUT BACK 18" IN-INTHE FRONT
AND BACK OF THE EARS, THIS IS TO
MAKE THE EARS STAND OUT, THE
NOSE IS \$4" WIDE AT THE TIP
AND TAPERS BACK TO THE HEAD.
THE DOTTED LINES ON THE HEAD
IN PICTURE (2) SHOWS THE ORIGINAL
WIDTH OF THE BLOCK ONLY.





GUT OUT THE SHADED PARTS SHOWN HERE:
THE EYE IS A DEEP NOTCHCUT DOWN INTO THE HEAD AND CUT OUT. ROUND OFF THE NOSE AS SHOWN IN THE SHADED AREAS.









THE EARS ARE COMPLETED AT THIS TIME. CUT OUT THE WASTE FROM BETWEEN THEM-LEAVING THE EARS ABOUT 18" THICK, ROUND OFF THE EDGES ALSO.

THE PARTS OF THE DOG,
SANDPAPER IT TO A SMOOTH
ROUNDNESS. WHEN USING
THE SANDPAPER, ALWAYS
GO WITH THE GRAIN OF
THE WOOD. IT MAKES A
CLEANER JOB.



